



规格说明:Specifications:

电气特性:Electrical:

1. 额定电流: Current Rating  
1.5A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:  
1000MEGA ohms MIN

物理性能:Mechanical:

1. 插拔力: Connector Mate and Unmate Force  
Mate force:3.75kgf(MAX)  
Unmate force:1.02kgf(MIN)
2. 端子保持力: Terminal Retention  
1.2kgf(MIN)

原材料:Material:

1. 塑胶:Housing:  
Hing Temperature Thermaplastics,  
UI 94V-0 PBT/LCP White/Black
2. 端子:Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

1. 端子:Contact: Plated Gold in Mating Area;  
Tin On Solder Tails
2. 外壳:Shell:  
Nickel Plating

设计/Designed by	绘图/Drawing by	审核/Checked by	批准/Approved by	未注公差 General Tolerance	
				x. ±0.5	x.° ±2°
		图名/File name	文件编号/File No.	.x ±0.3	.x° ±1°
		178产品图	页序/Sheet	.xx ±0.2	.xx° ±0.5°
				.xxx ±0.1	
备注/Remark				单位/Units: mm	