



300V 15A 2.5mm²
 Poles: 2-24P
 Pitch: 5.08mm(.200")

Materials
 Housing: PA66 (UL 94V-0)
 Contact Phosphor Bronze, Nickel Plated.
 Wire Cage: Brass (Nickel Plated) or Steel (zinc plated)
 Screw: M2.5, Steel, A3 Zinc Plated.
 Torque: 0.4N.m

| | | | | | | |
|-----------------|----------------|----------------|-----------------|---------------------------|--------|-------------|
| 设计 /Designed by | 绘图 /Drawing by | 审核 /Checked by | 批准 /Approved by | 未注公差 General Tolerance | | |
| | | | | x. | ± 0.2 | x." ± 2' |
| | | 图名 /Title | 文件编号 /File No. | .x | ± 0.1 | .x' ± 1' |
| | | XY2500FB-5.08 | QJ/XYT-2270200 | .xx | ± 0.05 | .xx' ± 0.5' |
| | | 产品图 | 页序 /Sheet | .xxx | ± 0.01 | |
| | | 备注 /Remark | | 单位 /Units: mm | | |

| | | | |
|------------|---------------------|---------------|----------|
| 序号 /RevNo. | 更改记录 /Revision note | 签名 /Signature | 日期 /Date |
|------------|---------------------|---------------|----------|