



ITEM NO	ITEM	DESCRIPTION	UNIT	QTY
B	ELECTRICAL CHAR	INSULATION RESISTANCE:500M-OHM MIN CONTACT RESISTANCE:20M-OHM MAX RATING CURRENT:1.5A MIN DIELECTRIC VOLLAGE:1000RMS 60 SEC MIN	PCCS	

A	PHYSICAL CHAR	HOUSING:PBT 20% GLASS FILLED (UL94V-0) BLACK SPRING WIRE:0.35MM THICKNESS PHOSPHOR BRONZE ALLOY OVER NICKEL PLATED&CONTACT AREA WITH GOLD FLASH GOLD PLATED TEMPERATURE RANGE:-25+90C DURABILITY:500MATING CYCLES MIN	PCCS	
---	---------------	---	------	--

TOLERANCE GENERALES				
PLASTIC DIMENSION	X	XX	XXX	CABLE LENGTH
(tolerance(±))	1	0.5	0.20	(tolerance(±))
				2%

CHECKED	DRAW	SRP	UNIT	MM
INSPECTED	CUS.PART NO.		SCALE	1:1
APPROVED	CUSTOMER		DATE	01/08/10
TITLE	TL321BX641U0Y			
DRAWING NO.	D0942	REV	A	