



KGS-510F Ver.B



Web Smart 6-Port Gigabit Ethernet Switch with 1 GbE SFP Port

Product Highlights:

- Compact design
- Web management
- One 1000M SFP fiber
- DHCP support
- 802.1Q Tagged VLAN support
- QoS WFQ support
- Port mirroring function
- 802.1x port access control
- 802.1w RSTP, MSTP
- LACP link aggregation

Key Features:

- Provides 5 10/100/1000Mbps RJ-45 and one 1000M SFP
- Provides in-band web-based management interface
- All copper ports support auto-negotiation and auto-MDI/MDI-X detection
- Provides full wire speed forwarding
- Supports 802.3x flow control for full-duplex and backpressure for half-duplex
- Provides port status, statistic monitoring and control function
- Supports DHCP IP configurafion
- Supports port-based and 802.1Q Tag-based VLAN
- Provides QoS function
- Provides port link aggregation (trunking) function with LACP support
- Provides port mirroring function
- Provides 802.1x authentication for port access
- Supports 802.1w RSTP and MSTP
- Watchdog timer function

Specifications:

Standard	IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1w, 802.1x, 802.3ad, 802.1Q
Network Ports	5 10/100/1000Mbps Gigabit copper ports Shielded RJ-45, auto-negotiation, auto-MDI/MDI-X support 1 1000Mbps Gigabit fiber SFP port SFP supports standard SFP fiber transceiver installation
Network Cables	10/100Mbps: Cat.5 up to 100m, 1000Mbps: Cat.5e or higher up to 100m
MAC Address Table	8K entries
Buffer Memory	112KB
VLAN	Port based VLAN, 8021Q Tag-based VLAN
Port Link Aggregation	Trunking groups: 4 max., Ports/group: 6, LACP (802.3ad) support
QoS	4 priority queues, Classification: Port-based, 802.1p, IP DSCP
LED Indication	Per unit: Power Per copper port: 1000M, 100M, 10M speed/link/activity status SFP port: 1000M speed/link/activity status, Optical link status
Management Support	Web browser software, SNMP MIB-2
Management Objects	System settings, port status/statistics, port control, VLAN, QoS, Link aggregation, port mirroring, Firmware upgrade, 802.1w RSTP, 802.1x, Configuration backup and restore
Environment	Operating Temperature: 0°C ~ 40°C (Main device) Storage Temperature: -20°C ~ 70°C Relative Humidity: 10% ~ 90% non-condensing (* The operating temperature range of the bundled power adapter may differ from the temperature range of the main device.)



Dimension	144 x 104.5 x 26 mm (WxDxH)
Power Input	+5V ~ +12VDC (+/-5%) via external power adapter
Power Consumption	5W max. @+5V (DC IN)
Approval	FCC Class A, CE mark Class A

Fiber Optical Specifications:

Model	Connector	Fiber	Wavelength	Tx Power	Rx Sens.	Rx Max.	Distance
-SX	LC	62.5/125 MMF 50/125 MMF	850nm	-9.5 ~ -4dBm	-18dBm	-1dBm	200m 500m
-LX	LC	MMF SMF	1310nm	-9.5 ~ -3dBm	-20dBm	-3dBm	550m 10km
-LX20	LC	SMF	1310nm	-7 ~ 0dBm	-24dBm	-3dBm	20km
-LX30	LC	SMF	1310nm	-4 ~ +3dBm	-23dBm	-3dBm	30km
-LX50	LC	SMF	1550nm	-4 ~ +1dBm	-23dBm	-3dBm	50km
-LX70	LC	SMF	1550nm	0 ~ +5dBm	-23dBm	-3dBm	70km
-W3510	Bi-Di LC	SMF	Tx 1310nm Rx 1550nm	-9 ~ -3dBm	-21dBm	-3dBm	10km
-W5310	Bi-Di LC	SMF	Tx 1550nm Rx 1310nm	-9 ~ -3dBm	-21dBm	-3dBm	10km
-W3520	Bi-Di LC	SMF	Tx 1310nm Rx 1550nm	-8 ~ -3dBm	-23dBm	-3dBm	20km
-W5320	Bi-Di LC	SMF	Tx 1550nm Rx 1310nm	-8 ~ -3dBm	-23dBm	-3dBm	20km
-W3410	Bi-Di LC	SMF	Tx 1310nm Rx 1490nm	-9 ~ -3dBm	-20dBm	-3dBm	10km
-W4310	Bi-Di LC	SMF	Tx 1490nm Rx 1310nm	-9 ~ -3dBm	-20dBm	-3dBm	10km
-W3410S	Bi-Di SC	SMF	Tx 1310nm Rx 1490nm	-9 ~ -3dBm	-20dBm	-3dBm	10km
-W4310S	Bi-Di SC	SMF	Tx 1490nm Rx 1310nm	-9 ~ -3dBm	-20dBm	-3dBm	10km



FCC Part 15, Class A
CISPR 22 Class A

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-chih, New Taipei City, Taiwan, R.O.C.
Tel: 886-2-2698-3878
Fax: 886-2-2698-3873
E-mail: kti@ktinet.com.tw
URL: http://www.ktinet.com.tw

KTI Networks Inc.

10415-A Westpark Drive, Houston,
TX 77042. U.S.A.
Tel: 1-713-266-3891
Fax: 1-713-914-0555
E-mail: contact@ktinet.com
URL: http://www.ktinet.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Application Example

Edge workgroup switch with uplink to 802.1Q tagged backbone network via 1000M fiber

