



SPECIFICATIONS :

Suitable Rated Current : 10A Max.

Dielectric Strength for 60 seconds : AC1500V Min.

Contact Resistance at 1A DC : 5mΩ Max.

Insulation Resistance at 500V DC : 100MΩ Min.

Molded Parts : Nylon

Wire : 18#AWG / 8"Loop

Style : Bayonet Type

Tolerances : Unless Otherwise Specified

Dimension	Critical To Function	General
< 1	+/- 0.02	+/- 0.03
1 ~ 8	+/- 0.1	+/- 0.2
8 ~ 24.995	+/- 0.15	+/- 0.25
25 ~ 99.99	+/- 0.2	+/- 0.3
Angles	+/- 1°	+/- 5°

Rev	EN	Description	Dwg	Ckd	Appd	Date
B	93092401	Modify the tolerance	Kao	Chyi	Ku	2004/9/24

Material	Drawn		Title: In-Line Fuse Holder				
	Check						
Finish	Engr		A	GTQD-HLD-1827-0502	B		
	Appd						
Unless Otherwise Specified Dimensions are mm (inch) Tolerances: .x = 1.0 (.04) .xx = 0.5 (.02) .xxx = 0.25 (.010)			Scale:	1:1	Dwg Size	Sht 1 of 1	Rev
Model File Name : In-Line Fuse Holder for 5x20mm Fuses							
Drawing File Name : GTQD-HLD-1827-0502							
Part Number : 1827 0502 421					Date:	2004/9/24	