




motor



Reference number Referencia	Nominal voltage Tensión nominal	Nominal torque Par nominal	Nominal speed Velocidad nominal	Nominal current Corriente nominal	Starting torque Par de arranque	Starting current Corriente de Arranque	Shaft Eje	Connections Conexiones	Wiring diag. Esq. elect.	Approximate weight Peso aproximado	Watertightness Grado de estanqueidad	Design: a,b Diseño: a,b	Curve Curva
	Un (V)	Mn (N.m./Lbf.in)	nn (r.p.m.)	In (A)	Ma (N.m./Lbf.in)	Ia (A)				P (kg / Lb.t)	IP		
162.4101.20.00	12	0.18 / 1.59	2800	7.5	1.0 / 8.85	33	E2	C2	EE2	1.1 / 2.95	IP53	a	32
162.4101.30.00	24	0.20 / 1.77	3000	4	1.0 / 8.85	18	E2	C2	EE2	1.1 / 2.95	IP53	a	33
162.4102.20.00	12	0.20 / 1.77	2000	6	1.0 / 8.85	24	E2	C3	EE2	1.1 / 2.95	IP53	a	34
162.4102.30.00	24	0.20 / 1.77	2000	3	1.0 / 8.85	12	E2	C3	EE2	1.1 / 2.95	IP53	a	34
162.4106.20.00	12	0.18 / 1.59	2800	7.5	1.0 / 8.85	33	E4	C2	EE2	1.1 / 2.95	IP53	a	32
162.4106.30.00	24	0.20 / 1.77	3000	4	1.0 / 8.85	18	E4	C2	EE2	1.1 / 2.95	IP53	a	33
162.4107.30.00E	24	0.20 / 1.77	2000	3	1.0 / 8.85	12	E5	C5	F3	1.1 / 2.95	IP53	a	34
162.4108.30.00	24	0.18 / 1.59	1500	2.5	0.8 / 7.08	8.5	E2	C3	EE2	1.1 / 2.95	IP53	a	35
162.4109.30.00	24	0.18 / 1.59	1500	2.5	0.8 / 7.08	8.5	E38	C35	EE3	1.1 / 2.95	IP53	a	35
162.4109.50.00	48	0.18 / 1.59	1500	1,3	0.8 / 7.08	4,5	E38	C35	EE3	1.1 / 2.95	IP53	a	35
162.4113.30.00	24	0.12 / 1.06	3000	2.5	1.0 / 8.85	15	E3	C4	F3	1.1 / 2.95	IP40	a	36
162.4116.30.00	24	0.20 / 1.77	3000	4	1.0 / 8.85	18	E58/E57	C2	EE2	1.1 / 2.95	IP40	b	33

