



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55C TO 105C.

MECHANICAL CHARACTERISTICS:

CONTACT INSERTION FORCE: KG MAXIMUM.
 CONTACT SEPARATION FORCE: KG MINIMUM.

MATERIALS:

CONTACT: BRASS..
 INSULATOR: P.B.T. UL 94-V0 RATED.
 SHELL: COLD ROLLED STEEL.

FINISHES:

CONTACTS: GOLD FLASHED.
 SHELL: NICKEL, TIN, ZINC PLATED.

A	前鉚型(不通孔)	B	後鉚型 (通孔)

PART NO.	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25	F±0.25
HDS-15S	30.80	25.00	16.33	7.90	12.60	5.90
HDS-26S	39.20	33.32	24.66	7.90	12.60	5.90
HDS-44S	53.05	47.04	38.38	7.90	12.60	5.90
HDS-62S	69.40	63.50	54.84	7.90	12.60	5.90

力壯實業有限公司					
PART NAME		H.D. D-SUB FEMALE SOLDER TYPE			
DWG.NO.	HC-043	SCALE	1:1	DATE	2001.03.05
CHECK		UNIT	mm	NAME	