



SPECIFICATION

- A: MATERIAL:
 1. HOUSING: NYLON 66 FLAMMABILITY, UL 94V-0
 2. TERMINAL: COPPER ALLOY, TIN PLATED
- B: CHARACTERISTICS:
 1. RATING: 10A 250V~ NORTH AMERICA & EUROPE
 2. INSULATION RESISTANCE: 100 MΩ MIN, AT 500 VDC
 3. ELECTRIC STRENGTH: AC 2,000 V FOR 1 MINUTE
- C: APPROVALS:
 UL, CSA, VDE, ENEC, KC & CCC

研發部資料分發章
 2012.05.18
 華瑋電子(東莞)有限公司

暫行使用章

E			
D			
C			
B	2012.03.20	DGRXXXXX	CHANGE SAFETY MARK
A	2006.04.18	DGR06033	NEW REVISION
REV	DATE	DOCUMENT	DESCRIPTION

TOLERANCE UNLESS OTHERWISE MARKED		PART NO.:	NAME:
DIMENSION:		0717-2-CQ00	AC INLET 3P+FUSE HOLDER
ANGULAR:			(SCREW-ON)
.000: ±0.1		MATERIAL:	SPEC.:
.00 : ±0.2		SEE ABOVE	IEC 60320-1, C14
.0 : ±0.3		APPROVED	IEC 60127-6
		CHECKED	DESIGNER NOTE:
		林	王
		2012 MAY 17	2012-05-17
		家慶	泉永
		UNIT	SCALE
		mm	1 : 1
		SHEET	1 of 1
		DOC#	5717-0039