


Mod. AU
Terminal preaislado horquilla


Los terminales preaislados AU están fabricados con fleje de cobre electrolítico siendo el aislamiento en PVC.


RANGO / DIMENSIONES DEL PRODUCTO

Código	Ref.	Sección	Métrico	Dimensiones				Espesor	Kg x 1000	Bolsa / Caja
				T	ØI	A	L			
275100	AU-1,5/3	● 1,5	3	3,2	4,0	5,8	21,0	0,8	0,704	100/1500
275110	AU-1,5/4		4	4,3		6,4	20,6		0,648	100/1500
275120	AU-1,5/5		5	5,3		8,5	21,0		0,836	100/1000
275130	AU-1,5/6		6	6,4		12,0	27,2		1,226	100/1000
275140	AU-1,5/8		8	8,4		14,0	26,3		0,846	100/1000
275150	AU-1,5/10	10	10,5	17,5	30,8	0,910	100/500			
275160	AU-2,5/3	● 2,5	3	3,2	4,8	5,9	21,0	0,8	0,824	100/1200
275170	AU-2,5/4		4	4,3		6,4	20,6		0,782	100/1000
275180	AU-2,5/5		5	5,3		9,5	22,0		0,966	100/1000
275190	AU-2,5/6		6	6,4		12,0	27,2		1,406	100/800
275200	AU-2,5/8		8	8,4		14,0	26,3		1,222	100/800
275210	AU-2,5/10	10	10,5	17,5	30,8	1,092	100/300			
275220	AU-6/4	● 6,0	4	4,3	7,0	8,5	27,2	1,0	1,778	100/500
275230	AU-6/5		5	5,3		9,5	26,7		1,740	100/500
275240	AU-6/6		6	6,4		13,5	32,7		2,488	100/500
275250	AU-6/8		8	8,4		13,5	32,7		2,274	100/400
275260	AU-6/10		10	10,5		15,5	35,0		2,106	100/400