

P:	M-Y417B	Customer No:	
	M-417A		
	P3: M-427B		

DB9 M

P1

PIN6

PIN1

PIN9

PIN5

P

62.5±0.5

P3

①

④

③

②

DB25 M

P2

PIN13

PIN25

PIN1

PIN14

4025

P1

1

2

3

4

5

6

7

8

9

SHIELD

P2

8

3

2

20

7

6

4

5

22

SHIELD

*NOTE: All relevant materials are complied with RoHS directive .

4	UL1061 26AWG INSULATOR, LENGTH 47mm&55mm, DRAWING NO. EH002601C-013	10	M304
	MOLDED PE COLOR TRANSPARENT		TWN
	MOLDED PVC BEIGE		M304
3	MOLDED THUMBSCREW #4-40, LENGTH 21.5mm, BEIGE	4	M95
2	DB25 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
1	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
No.	DESCRIPTION	Q'TY	Supplier
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm	
CHECKED	TIAN		
DRAWING	XIE		
DATE	03/JUL/06		
ITEM NO.	4025	UNIT:mm	

CHECKED